

Gotco International
Fishing Bumper Sub Strength Table

Part No.	O.D.	I.D.	Tensile Strength (lbs)	Torque (ft-lbs)
BSK-5	1- 13/16	3/8	71,550	880
**BSK-15	2-1/4	1/2	129,000	1,700
BSK-25	3-1/8	1-17/32	165,500	4,430
BSK-30	3-5/32	1	190,900	4,700
BSK-34	3-3/8	1	217,600	5,500
BSK-36	3-3/4	1-1/2	240,550	7,130
**BSK-40	3-3/4	1-1/4	285,300	6,100
BSK-41	3-3/4	1-7/8	258,000	6,700
BSK-42	4-1/8	1-1/2	315,000	11,150
BSK-44	4-1/2	2-3/8	294,000	14,300
BSK-46	4-1/4	1-15/16	302,200	9,900
BSK-50	4-5/8	2	322,250	15,000
BSK-54	4-3/4	1-1/2	488,500	16,200
BSK-56	4-3/4	2	403,800	15,000
BSK-69	5-3/4	2	568,300	27,700
BSK-74	6-1/8	2-1/4	758,300	44,650
BSK-75	6-1/4	2-1/4	865,200	44,650
BSK-76	6	2	713,000	27,700
BSK-85	6-3/4	2-3/4	761,000	39,200
BSK-101	7-3/4	3-1/2	761,600	38,200
**BSK-102	8	3-1/2	968,700	38,200
BSK-105	9	4	1,443,900	115,250
BSK-312	3-1/8	1	177,430	4,700
BSK-600	6	2	717,150	27,700
**BSK-650	6-1/2	2-1/4	1,085,000	44,600
**BSK-675	6-3/4	2-1/4	1,088,000	44,600
BSK-700	7	2-3/4	997,000	39,200
**BSK-812	8-1/8	3-1/2	968,700	38,200
**BSK-825	8-1/4	3-1/2	968,700	38,200
**BSK-850	8-1/2	3-1/2	968,700	38,200
**BSK-950	9-1/2	4	2,040,200	115,000
**BSK-1000	10	4	2,040,200	115,000

Note: Strength values listed are considered accurate to within plus or minus 15% and are intended to be used for a guideline only. This does not imply a guarantee for this product. All calculations were based on the minimum yield strength of the material used for manufacturing of the product.

***Indicates that the mandrel tensile strength was less than that of the barrel, so calculated values are based on the mandrel, not the barrel for that assembly.*